



FCC TEST REPORT

For

SHENZHEN NSE ELECTRONICS CO., LTD

Indoor LED Screen

Test Model: P1.2


Additional Model No.: Please Refer to Page 8

Prepared for : SHENZHEN NSE ELECTRONICS CO., LTD
1F, Bld No.1, YaLi Ind park, No.13 TianBao Rd,
Address : YingRenShi, Shiyan town, BaoAn district, Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Room 101, 201, Building A and Room 301, Building C,
Address : Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel : +(86) 0755-82591330
Fax : +(86) 0755-82591332
Web : www.lcs-cert.com
Mail : webmaster@lcs-cert.com

Date of receipt of test sample : October 12, 2024
Number of tested samples : 1
Serial number : Prototype
Date of Test : October 12, 2024 to October 23, 2024
Date of Report : October 24, 2024



**TEST REPORT****Report No.** : **LCSA10084179E****Date of Issue** : October 24, 2024**Testing Laboratory Name** : **Shenzhen LCS Compliance Testing Laboratory Ltd.****Address** : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China**Testing Location/ Procedure** : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name** : **SHENZHEN NSE ELECTRONICS CO., LTD****Address** : 1F, Bld No.1, YaLi Ind park, No.13 TianBao Rd, YingRenShi, Shiyan town, BaoAn district, Shenzhen, China**Test Specification****Standard** : FCC 47 CFR Part 15, Subpart B
ANSI C63.4-2014**Test Report Form No.** : TRF-4-E-010 A/0**TRF Originator** : Shenzhen LCS Compliance Testing Laboratory Ltd.**Master TRF** : Dated 2011-03**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : **Indoor LED Screen****Trade Mark** : NSE**Test Model** : P1.2**Result** : **Positive****Compiled by:**

Zi Liao

Zi Liao / File Administrator

Supervised by:

Cary Luo

Cary Luo/ Technique principal

Approved by:

Gavin Liang / Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



TEST REPORT

Test Report No.: LCSA10084179E	<u>October 24, 2024</u> Date of issue
---------------------------------------	--

Test Model	: P1.2
EUT	: Indoor LED Screen
Applicant	: SHENZHEN NSE ELECTRONICS CO., LTD
Address	: 1F, Bld No.1, YaLi Ind park, No.13 TianBao Rd, YingRenShi, Shiyan town, BaoAn district, Shenzhen, China
Telephone	: /
Fax	: /
Manufacturer	: SHENZHEN NSE ELECTRONICS CO., LTD
Address	: 1F, Bld No.1, YaLi Ind park, No.13 TianBao Rd, YingRenShi, Shiyan town, BaoAn district, Shenzhen, China
Telephone	: /
Fax	: /
Factory	: SHENZHEN NSE ELECTRONICS CO., LTD
Address	: 1F, Bld No.1, YaLi Ind park, No.13 TianBao Rd, YingRenShi, Shiyan town, BaoAn district, Shenzhen, China
Telephone	: /
Fax	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.



Shenzhen LCS Compliance Testing Laboratory Ltd.
Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com
Scan code to check authenticity



Revision History

Report Version	Issue Date	Revision Content	Revised By
000	October 24, 2024	Initial Issue	/





TABLE OF CONTENTS

Test Report Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	6
1.1 Description of Standards and Results	6
1.2 Description of Test Modes	7
2. GENERAL INFORMATION	8
2.1 Description of Device (EUT)	8
2.2 Support equipment List	8
2.3 Description of Test Facility	8
2.4 Measurement Uncertainty	8
3. MEASURING DEVICES AND TEST EQUIPMENT	9
4. EMISSION TEST RESULTS (EMI)	10
4.1 Conducted emissions on AC mains	10
4.2 Radiated emissions (Below 1GHz)	13
5. TEST SETUP PHOTOS	16
6. EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)	17





1. SUMMARY OF STANDARDS AND RESULTS

1.1 Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

Description of Test Item	Standard	Limits	Result
Conducted emissions on AC mains	FCC 47 CFR Part 15, Subpart B ANSI C63.4-2014	15.107, Class A	Pass
Radiated emissions (Below 1GHz)	FCC 47 CFR Part 15, Subpart B ANSI C63.4-2014	15.109, Class A	Pass





1.2 Description of Test Modes

No	Title	Description
TM1	Working (AC 120V/60Hz)	Record





2. GENERAL INFORMATION

2.1 Description of Device (EUT)

EUT	: Indoor LED Screen
Test Model	: P1.2
Additional Model No.	: P1.5, P1.6, P1.8, P1.9, P2, P2.5, P2.6, P2.8, P2.9, P3, P3.9, P4, P4.8
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.
Power Supply	: Working voltage:100-230V~ Avg.Power: 146W
Highest Internal Frequency	: 1.705-108MHz
Classification of Equipment	: Class A

Highest internal frequency (Fx)	Highest measured frequency
$F_x \leq 1.705\text{MHz}$	30MHz
$1.705\text{MHz} < F_x \leq 108\text{MHz}$	1GHz
$108\text{MHz} < F_x \leq 500\text{MHz}$	2GHz
$500\text{MHz} < F_x \leq 1000\text{MHz}$	5GHz
$F_x > 1\text{GHz}$	5 x Fx up to a maximum of 40GHz

2.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
/	/	/	/	/

2.3 Description of Test Facility

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

2.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emission (150kHz to 30MHz)	$\pm 2.35 \text{ dB}$
Radiated Emission (30MHz to 1000MHz)	$\pm 3.48 \text{ dB}$
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	





3. MEASURING DEVICES AND TEST EQUIPMENT

Conducted emissions on AC mains

Equipment	Manufacturer	Model No	Serial No.	Cal Date	Due Date
EMI Test Software	Farad	EZ	/	/	/
Artificial Mains	R&S	ENV216	101288	2024-06-06	2025-06-05
Pulse Limiter	R&S	ESH3-Z2	102750-NB	2024-06-06	2025-06-05
EMI Test Receiver	R&S	ESR3	102312	2024-03-02	2025-03-01

Radiated emissions (Below 1GHz)

Equipment	Manufacturer	Model No	Serial No.	Cal Date	Due Date
EMI Test Software	Farad	EZ	/	/	/
EMI Test Software	AUDIX	E3	/	/	/
By-log Antenna	SCHWARZBECK	VULB9163	01143	2024-07-20	2027-07-19
Horn Antenna	SCHWARZBECK	3115	EABF-018	2024-07-20	2027-07-19
EMI Test Receiver	R&S	ESR3	102311	2024-06-06	2025-06-05
Broadband Preamplifier	/	BP-01M18G	P190501	2024-06-06	2025-06-05
EMI Test Receiver	R&S	ESCI7	101173	2023-10-25	2024-10-24
By-log Antenna	SchwarzZBECK	VULB9163	01565	2024-07-13	2027-07-12





4. EMISSION TEST RESULTS (EMI)


4.1 Conducted emissions on AC mains

Test Requirement:	15.107, Class A		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dBμV)	
		Quasi-peak	Average
	0.15-0.5	79	66
	0.5-30	73	60
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.4-2014		
Procedure:	An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected. Remark: Level= Read Level+ Cable Loss+ LISN Factor		

4.1.1 E.U.T. Operation:

Operating Environment:			
Temperature:	22.7 °C	Humidity:	53.7 %
Pre test mode:	TM1		
Final test mode:	TM1		


4.1.2 Test Setup Diagram:





4.1.3 Test Data:

TM1 / Line: Line




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.152	48.08	19.63	67.71	79.00	-11.29	QP	
2		0.152	32.78	19.63	52.41	66.00	-13.59	AVG	
3		0.272	41.16	19.63	60.79	79.00	-18.21	QP	
4		0.272	28.63	19.63	48.26	66.00	-17.74	AVG	
5		0.866	44.67	19.64	64.31	73.00	-8.69	QP	
6		0.866	30.10	19.64	49.74	60.00	-10.26	AVG	
7		5.550	42.64	19.70	62.34	73.00	-10.66	QP	
8		5.550	29.48	19.70	49.18	60.00	-10.82	AVG	
9		12.502	33.92	19.84	53.76	73.00	-19.24	QP	
10		12.502	32.70	19.84	52.54	60.00	-7.46	AVG	
11		17.813	33.58	20.13	53.71	73.00	-19.29	QP	
12	*	17.813	32.50	20.13	52.63	60.00	-7.37	AVG	





TM1 / Line: Neutral



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV	dBuV	dB		
1	*	0.150	51.85	19.63	71.48	79.00	-7.52	QP	
2		0.150	38.40	19.63	58.03	66.00	-7.97	AVG	
3		0.263	46.16	19.63	65.79	79.00	-13.21	QP	
4		0.263	34.99	19.63	54.62	66.00	-11.38	AVG	
5		0.857	42.36	19.64	62.00	73.00	-11.00	QP	
6		0.857	23.03	19.64	42.67	60.00	-17.33	AVG	
7		5.622	45.62	19.80	65.42	73.00	-7.58	QP	
8		5.622	31.42	19.80	51.22	60.00	-8.78	AVG	
9		12.498	34.33	19.84	54.17	73.00	-18.83	QP	
10		12.498	28.84	19.84	48.68	60.00	-11.32	AVG	
11		17.813	31.68	20.13	51.81	73.00	-21.19	QP	
12		17.813	30.00	20.13	50.13	60.00	-9.87	AVG	

***Note: 1) Pre-scan all modes and recorded the worst case results in this report.

2) Margin= Reading level + Correct factor-Limit

Correct Factor=Lisn Factor+Cable Factor+Insertion loss of Pulse Limiter



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




4.2 Radiated emissions (Below 1GHz)

Test Requirement:	15.109, Class A				
Test Limit:	Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:				
	Frequency of emission (MHz)	Field strength @3m		Field strength @10m	
		(uV/m)	(dBuV/m)	(uV/m)	(dBuV/m)
	30 – 88	90	39.1	300	49.5
	88 – 216	150	43.5	500	54.0
	216 – 960	210	46.4	700	56.9
	Above 960	300	49.5	1000	60.0
Test Method:	ANSI C63.4-2014				
Procedure:	An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor				

4.2.1 E.U.T. Operation:

Operating Environment:			
Temperature:	26.4 °C	Humidity:	54.2 %
Pre test mode:	TM1,TM2		
Final test mode:	TM1,TM2		


4.2.2 Test Setup Diagram:





4.2.3 Test Data:

TM1 / Polarization: Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	37.302	60.62	-18.20	42.42	49.50	-7.08	QP	P	
2 *	53.379	60.53	-16.68	43.85	49.50	-5.65	QP	P	
3	71.203	62.46	-20.54	41.92	49.50	-7.58	QP	P	
4	125.806	64.72	-21.23	43.49	54.00	-10.51	QP	P	
5	250.486	66.41	-17.09	49.32	56.00	-6.68	QP	P	
6	628.894	59.93	-9.99	49.94	56.00	-6.06	QP	P	





TM1 / Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 *	37.565	62.43	-18.12	44.31	49.50	-5.19	QP	P	
2	53.379	55.68	-16.68	39.00	49.50	-10.50	QP	P	
3	124.925	66.92	-21.06	45.86	54.00	-8.14	QP	P	
4	250.486	66.40	-17.09	49.31	56.00	-6.69	QP	P	
5	376.523	63.85	-14.80	49.05	56.00	-6.95	QP	P	
6	628.894	56.27	-9.99	46.28	56.00	-9.72	QP	P	

Note:1).Pre-Scan all mode, Thus record worse case mode result in this report.

2) Margin= Reading level + Correct factor – Limit

Correct Factor=Antenna Factor+Cable Factor- Pre-amplifier Factor



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity




5. TEST SETUP PHOTOS

Conducted emissions on AC mains



Radiated emissions (Below 1GHz)





6. EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS)



Fig. 1



Fig. 2





Fig. 3



Fig. 4





Fig. 5



Fig. 6





Fig. 7



Fig. 8






Fig. 9




Fig. 10






Fig. 11




Fig. 12





Fig. 13




Fig. 14






Fig. 15




Fig. 16





Fig. 17



Fig. 18





Fig. 19



Fig. 20

--- End of Report ---

